## A630/A631/A632

58 mm Thermal printer

## Desktep and pertable printer







### The printer of reference fer yeur desktep er pertable applications

The A630 series has been developed to meet the needs for an ultra-small-footprint and lightweight thermal printer featuring a wide range of printing capabilities.

The A631 is dedicated to portable applications requiring a receipt and especially to the ever-expanding world of mobile electronics such as PDAs, route sales and inventory control. In addition a carrying case is available for belt-hung/hands-free

For your desktop applications in the retail, EFT, medical, and test and measurement fields, Axiohm offers the desktop sister: A630. For the automotive application, a specific A632 version is available.

### Blueteeth™ technology makes the dream of wireless come true

Foreseeing how valuable Bluetooth™ technology would be for its customers and the ever-expanding world of mobile electronics, Axiohm developed a Bluetooth™ Class 2 version of its A631 printer. The battery-operated A631 can communicate with any equipment that contains an RF Bluetooth™ emitter. It can be used at a distance of up to 10 meters and has a data transmission rate of 1 Mb/second, guaranteeing excellent printer performance.

### Enriched features answering all your needs

Since Axiohm's attention is squarely focused on improvement and innovation, we offer many functionalities on the A630 series:

- Sleep mode with a wake up through the reset button or the communication cable
- Optimization of the battery life, up to 170 hours
- A design that responds to the special constraints of usage in a vehicle for the A632 version: 12VDC battery, 12V/9VDC converter, plastic casing capable of withstanding an extended operating/storage temperature, 'e' certification (95/94/EC)
- Driver SDK available to develop your own application on your

**-**Axiohm

A630/A631/A632 (0205



# A630/A631/A632

58 mm Thermal printer

Characteristics	Unit	A630/A632		A631
Printing speed (max)	mm/s	55		50
Printing width	mm		48	
Resolution	dot/mm	8		
Number of dots	dot	384		
Columns	column	24 or 40		
Character size	dot*dot	9*24 or 16*24		
Resident code page		CP437		
Bar code type		UPC-A, UPC-E, EAN 8&13, code 39, ITF		
Paper width	mm	58		
Paper roll diameter	mm	50		
Paper roll thickness	μm	Up to 80		
Paper loading		Clamshell™		
Operating voltage range	V	9V (A630) or 12V (A632)		6V (NIMH battery)
Current consumption	А	2.5		
Head pulse life	pulse	0.5*10°		
Mechanical reliability	km	50		
Dimensions (W*D*H)	mm	108*147*72		
Weight	g	330		550
Operating temperature	°C/F	0 to 50/32 to 122		
Operating humidity	%RH	10 to 85		
Cutter		Manual tear bar		
Data buffer	Kbytes	4		
Flash memory	Kbytes	64		
Interface		RS232/Centronics		2/Centronics, Bluetooth™ Class 2
Driver		Windows™ 98/00/XP		
Emulation		ESC/POS™		
CEM & Safety standards		UL/CAS60950, IEC/EN60950, CE Class B, FCC Class A, C-Tick		
Added features		Desktop Easyfont		Portable Easyfont
Options		Carrying Case		
		12 to 9V converter for car application		

#### Other Axiohm's products



## Thermal Printer Mechanisms

Axiohm's thermal printer mechanisms meet the most demanding market needs in terms of printing speed (up to 250 mm/s), paper width (60 mm, 2\*38 mm, 80 mm & 82.5 mm), ruggedness, compactness, both easy integration and use.



### Turnkey Printing Selutions

AXIOHM's kiosk printers are designed primarily for installation in public access terminals, but can be used in almost any transaction printing application that requires an easy-to-integrate "plug & play" product.



#### Centreller Beards

Axiohm offers an extensive range of controller boards with embedded firmware to manage its full line of thermal printer mechanisms. The controller boards' features have been designed to meet your needs in terms of functionality and competitiveness.

-Axiohm

France (for EMEA & Asia/Pacific)
1, rue d'Arcueil - BP 820
92542 Montrouge Cedex - FRANCE
Tel: +33 1 58 07 17 17
Fax: +33 1 58 07 17 18
info@axiohm.com

USA 455 Wards Corner Road Suite 500 Loveland, OH 45140 - USA Tel: +1 (513) 248-9900 Fax: +1 (513) 248-8274 namsales@axiohm.com www.axiehm.cem